

Zeners 1N4678 - 1N4702

Absolute Maximum Ratings * T_A = 25°C unless otherwise noted

Symbol	Parameter	Value	Units
P _D	Power Dissipation @ TL ≤ 75°C, Lead Length = 3/8"	500	mW
	Derate above 75°C	4.0	mW/°C
T _J , T _{STG}	Operating and Storage Temperature Range	-65 to +200	°C

* These ratings are limiting values above which the serviceability of the diode may be impaired.



Electrical Characteristics T_A = 25°C unless otherwise noted

Device	V _Z (Volts) @ I _Z = 50μA (Note 1)			I _R @ V _R		I _{ZM} (mA) (Note 2)	ΔV _Z (Volts) (Note 3)
	Min.	Typ.	Max.	μA	Volts		
1N4678	1.71	1.8	1.89	7.5	1	120	0.7
1N4679	1.9	2	2.1	5	1	110	0.7
1N4680	2.09	2.2	2.31	4	1	100	0.75
1N4681	2.28	2.4	2.52	2	1	95	0.8
1N4682	2.565	2.7	2.835	1	1	90	0.85
1N4683	2.85	3	3.15	0.8	1	85	0.9
1N4684	3.135	3.3	4.465	7.5	1.5	80	0.95
1N4685	3.42	3.6	3.78	7.5	2	75	0.95
1N4686	3.705	3.9	4.095	5	2	70	0.97
1N4687	4.085	4.3	4.515	4	2	65	0.99
1N4688	4.465	4.7	4.935	10	3	60	0.99
1N4689	4.845	5.1	5.355	10	3	55	0.97
1N4690	5.32	5.6	5.88	10	4	50	0.96
1N4691	5.89	6.2	6.51	10	5	45	0.95
1N4692	6.45	6.8	7.14	10	5.1	35	0.9
1N4693	7.125	7.5	7.785	10	5.7	31.8	0.75
1N4694	7.79	8.2	8.61	1	6.2	29	0.5
1N4695	8.265	8.7	9.135	1	6.6	27.4	0.1
1N4696	8.645	9.1	9.555	1	6.9	26.2	0.08
1N4697	9.5	10	10.5	1	7.6	24.8	0.1
1N4698	10.45	11	11.55	0.05	8.4	21.6	0.11
1N4699	11.4	12	12.6	0.05	9.1	20.4	0.12
1N4700	12.35	13	13.65	0.05	9.8	19	0.13
1N4701	13.3	14	14.7	0.05	10.6	17.5	0.14
1N4702	14.25	15	15.75	0.05	11.4	16.3	0.15

V_F Forward Voltage = 1.5V Max @ I_F = 100mA

Notes:

- Zener Voltage (V_Z)
The zener voltage is measured with the device junction in the thermal equilibrium at the lead temperature (T_L) at 30°C ± 1°C and 3/8" lead length.
- Maximum Zener Current Ratings (I_{ZM})
The maximum current handling capability on a worst case basis is limited by the actual zener voltage at the operation point and the power derating curve.
- Maximum Voltage Change (ΔV_Z)
Voltage change is equal to the difference between V_Z at 100μA and at 10μA.

TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

ACEx™	FACT™	ImpliedDisconnect™	PACMAN™	SPM™
ActiveArray™	FACT Quiet Series™	ISOPLANAR™	POP™	Stealth™
Bottomless™	FAST®	LittleFET™	Power247™	SuperSOT™-3
CoolFET™	FASTr™	MicroFET™	PowerTrench®	SuperSOT™-6
CROSSVOLT™	FRFET™	MicroPak™	QFET®	SuperSOT™-8
DOME™	GlobalOptoisolator™	MICROWIRE™	QS™	SyncFET™
EcoSPARK™	GTO™	MSX™	QT Optoelectronics™	TinyLogic®
E ² CMOS™	HiSeC™	MSXPro™	Quiet Series™	TruTranslation™
EnSigna™	I ² C™	OCX™	RapidConfigure™	UHC™
Across the board. Around the world.™		OCXPro™	RapidConnect™	UltraFET®
The Power Franchise™		OPTOLOGIC®	SILENT SWITCHER®	VCX™
Programmable Active Droop™		OPTOPLANAR™	SMART START™	

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

PRODUCT STATUS DEFINITIONS

Definition of Terms

Datasheet Identification	Product Status	Definition
Advance Information	Formative or In Design	This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.
Preliminary	First Production	This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
No Identification Needed	Full Production	This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
Obsolete	Not In Production	This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only.