


MECHANICAL DATA

Dimensions in mm (inches)



TO-18 METAL PACKAGE

Underside View

PIN 1 – Source PIN 2 – Drain PIN 3 – Gate
 (Gate is connected to case)

**JFET SWITCHING
 N CHANNEL- DEPLETION**

FEATURES

- LOW ON RESISTANCE
- FAST SWITCHING
- MILITARY OPTIONS AVAILABLE

APPLICATIONS:

- SWITCHING APPLICATIONS

ABSOLUTE MAXIMUM RATINGS ($T_{case} = 25^{\circ}C$ unless otherwise stated)

| | | |
|-----------|--|-------------------------|
| V_{DS} | Drain–Source Voltage | 40V |
| V_{DG} | Drain–Gate Voltage | 40V |
| V_{GS} | Gate–Source Voltage | 40V |
| I_{GF} | Forward Gate Current | 50mA |
| P_D | Total Device Dissipation @ $T_C = 25^{\circ}C$ | 1.8W |
| | Derate above $25^{\circ}C$ | 10mW/ $^{\circ}C$ |
| T_J | Operating Junction Temperature Range | -65 to +175 $^{\circ}C$ |
| T_{STG} | Storage Temperature Range | -65 to +175 $^{\circ}C$ |

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise stated)

| Parameter | Test Conditions | Min. | Typ. | Max. | Unit |
|-------------------------------------|--|--|------|------|---------------|
| OFF CHARACTERISTICS | | | | | |
| $V_{(BR)GSS}$ | Gate Source Breakdown Voltage ¹ | $I_G = 1.0\mu\text{A}$ $V_{DS} = 0$ | 40 | | V |
| I_{GSS} | Gate Reverse Current | $V_{GS} = 20\text{V}$ $V_{DS} = 0$ | | 0.1 | nA |
| | | $V_{GS} = 20\text{V}$ $V_{DS} = 0$ $T_A = 150^\circ\text{C}$ | | 0.2 | μA |
| V_{GS} | Gate Source Voltage | $V_{DS} = 20\text{V}$ $I_D = 1.0\text{nA}$ | 4.0 | 10 | V |
| $V_{GS(f)}$ | Gate Source Forward Voltage | $I_G = 1.0\text{mA}$ $V_{DS} = 0$ | | 1.0 | V |
| $I_{D(off)}$ | Drain Cut-off Current | $V_{GS} = 12\text{V}$ $V_{DS} = 20\text{V}$ | | 0.1 | nA |
| | | $V_{GS} = 12\text{V}$ $V_{DS} = 20\text{V}$ $T_A = 150^\circ\text{C}$ | | 0.2 | μA |
| ON CHARACTERISTICS | | | | | |
| I_{DSS} | Zero Gate voltage Drain Current ¹ | $V_{GS} = 0\text{V}$ $V_{DS} = 20\text{V}$ | 50 | 150 | mA |
| $V_{DS(on)}$ | Drain Source On-Voltage | $I_D = 12\text{mA}$ $V_{GS} = 0$ | | 0.4 | V |
| $r_{DS(on)}$ | Static Drain Source On Resistance | $I_D = 1.0\text{mA}$ $V_{GS} = 0$ | | 30 | Ω |
| ELECTRICAL CHARACTERISTICS | | | | | |
| C_{iss} | Input Capacitance | $V_{GS} = 0\text{V}$ $V_{DS} = 20\text{V}$ $f = 1.0\text{MHz}$ | | 14 | pF |
| C_{rss} | Reverse Transfer Capacitance | $V_{GS} = 12\text{V}$ $V_{DS} = 0\text{V}$ $f = 1.0\text{MHz}$ | | 3.5 | |
| SMALL SIGNAL CHARACTERISTICS | | | | | |
| $r_{ds(on)}$ | Drain-Source "ON" Resistance | $V_{GS} = 0\text{V}$ $I_D = 0$ $f = 1.0\text{kHz}$ | | 30 | Ω |
| SWITCHING CHARACTERISTICS | | | | | |
| t_{on} | Turn-On Time | $I_{D(on)} = 12\text{mA}$ | | 15 | ns |
| t_{off} | Turn-Off Time | $V_{GS(on)} = 12\text{V}$ | | 20 | |
| t_r | RiseTime | $I_{D(on)} = 12\text{mA}$ | | 5.0 | |
| t_f | FallTime | $V_{GS(off)} = 12\text{V}$ | | 15 | |

- 1) Pulse test : Pulse Width < 300 μs ,Duty Cycle < 2%
- 2) f_t is defined as the frequency at which $|h_{fe}|$ extrapolates to unity.