

SANYO	No.3171	2SA1575/2SC4080
	PNP/NPN Epitaxial Planar Silicon Transistors High-Frequency Amp, Wide-Band Amp Applications	

Features

- High f_T
- High breakdown voltage
- Small reverse transfer capacitance and excellent high-frequency characteristic
- Adoption of FBET process

(): 2SA1575

Absolute Maximum Ratings at $T_a = 25^\circ\text{C}$

			unit
Collector to Base Voltage	V_{CBO}	(-)	200 V
Collector to Emitter Voltage	V_{CEO}	(-)	200 V
Emitter to Base Voltage	V_{EBO}	(-)	4 V
Collector Current	I_C	(-)	100 mA
Collector Current(Pulse)	I_{CP}	(-)	200 mA
Collector Dissipation	P_C		500 mW
Mounted on ceramic board ($250\text{mm}^2 \times 0.8\text{mm}$)			1.3 W
Junction Temperature	T_j		150 $^\circ\text{C}$
Storage Temperature	T_{stg}		- 55 to + 150 $^\circ\text{C}$

Electrical Characteristics at $T_a = 25^\circ\text{C}$

			min	typ	max	unit
Collector Cutoff Current	I_{CBO}	$V_{CB} = (-)150\text{V}, I_E = 0$			(-)0.1	μA
Emitter Cutoff Current	I_{EBO}	$V_{EB} = (-)2\text{V}, I_C = 0$			(-)1.0	μA
DC Current Gain	$h_{FE(1)}$	$V_{CE} = (-)10\text{V}, I_C = (-)10\text{mA}$	40*		320*	
	$h_{FE(2)}$	$V_{CE} = (-)10\text{V}, I_C = (-)60\text{mA}$	20			
Gain-Bandwidth Product	f_T	$V_{CE} = (-)30\text{V}, I_C = (-)30\text{mA}$		400		MHz
Output Capacitance	c_{ob}	$V_{CB} = (-)30\text{V}, f = 1\text{MHz}$		(2.3)1.8		pF
Reverse Transfer Capacitance	c_{re}	$V_{CB} = (-)30\text{V}, f = 1\text{MHz}$		(1.7)1.4		pF
C-E Saturation Voltage	$V_{CE(sat)}$	$I_C = (-)20\text{mA}, I_B = (-)2\text{mA}$			(-)1.0	V
B-E Saturation Voltage	$V_{BE(sat)}$	$I_C = (-)20\text{mA}, I_B = (-)2\text{mA}$			(-)1.0	V
C-B Breakdown Voltage	$V_{(BR)CBO}$	$I_C = (-)10\mu\text{A}, I_E = 0$	(-)200			V
C-E Breakdown Voltage	$V_{(BR)CEO}$	$I_C = (-)1\text{mA}, R_{BE} = \infty$	(-)200			V
E-B Breakdown Voltage	$V_{(BR)EBO}$	$I_E = (-)100\mu\text{A}, I_C = 0$	(-)4			V


* : The 2SA1575/2SC4080 are classified by 10mA h_{FE} as follows :

40	C	80	60	D	120	100	E	200	160	F	320
----	---	----	----	---	-----	-----	---	-----	-----	---	-----

Marking 2SA1575 : AF
 2SC4080 : CI
 h_{FE} rank : C,D,E,F

Package Dimensions 2038

(unit : mm)



(Bottom View) SANYO: PCP

SANYO Electric Co., Ltd. Semiconductor Business Headquarters
 TOKYO OFFICE Tokyo Bldg., 1-10, 1 Chome, Ueno, Taito-ku, TOKYO, 110 JAPAN

- No products described or contained herein are intended for use in surgical implants, life-support systems, aerospace equipment, nuclear power control systems, vehicles, disaster/crime-prevention equipment and the like, the failure of which may directly or indirectly cause injury, death or property loss.
- Anyone purchasing any products described or contained herein for an above-mentioned use shall:
 - ① Accept full responsibility and indemnify and defend SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors and all their officers and employees, jointly and severally, against any and all claims and litigation and all damages, cost and expenses associated with such use;
 - ② Not impose any responsibility for any fault or negligence which may be cited in any such claim or litigation on SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors or any of their officers and employees jointly or severally.
- Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.