

2SA561 is PNP silicon planar transistor designed for low power general purpose amplifiers.

TO-92B



ABSOLUTE MAXIMUM RATINGS

Collector-Base Voltage	VCBO	50V
Collector-Emitter Voltage	VCEO	50V
Emitter-Base Voltage	VEBO	5V
Collector Current	IC	150mA
Total Power Dissipation	Ptot	300mW
Operating Junction & Storage Temperature	Tj, Tstg	-55 to +150°C

ECB

ELECTRICAL CHARACTERISTICS (Ta=25°C)

PARAMETER	SYMBOL	MIN	MAX	UNIT	TEST CONDITIONS	
Collector-Emitter Breakdown Voltage	LVCEO	50		V	IC=10mA IB=0	
Collector Cutoff Current	ICBO		100	nA	VCB=18V IE=0	
Emitter Cutoff Current	IEBO		100	nA	VEB=5V IC=0	
D.C. Current Gain	HFE	70	400		IC=20mA VCE=1V	
Group O			140			
Group Y			240			
Group GR			400			
All group			23			
		23			IC=150mA VCE=5V*	
Group O						40
Group Y						67
Group GR						
Collector-Emitter Saturation Voltage	VCE(sat)		0.3	V	IC=100mA IB=10mA*	
Current Gain Bandwidth Product	fT	70	TYP	MHz	IC=1mA VCE=6V	
Output Capacitance	Cob	13	TYP	pF	VCB=6V f=1MHz	

* Pulse Test : Pulse Width <300us, duty cycle <2%.



MICRO ELECTRONICS LTD. 美科有限公司 FAX: 3-410321

38 Hung To Road, Kwun Tong, Kowloon, Hong Kong. Cable: Microtron, Hong Kong. Telex: 43510 Micro Hx.
P.O. Box 69477, Kwun Tong. Tel: 3-430181-6, 3-893363, 3-892423, 3-898224

M B P