

SANYO	No. 1251A	2SC3183
NPN Triple Diffused Planar Silicon Transistor HIGH-SPEED SWITCHING APPLICATIONS		

Features

- . High breakdown voltage ($V_{CBO} \geq 900V$).
- . High switching speed.
- . Wide ASO.

Absolute Maximum Ratings at $T_a=25^\circ C$

			unit
Collector-to-Base Voltage	V_{CBO}	900	V
Collector-to-Emitter Voltage	V_{CEO}	800	V
Emitter-to-Base Voltage	V_{EBO}	7	V
Collector Current	I_C	0.2	A
Peak Collector Current	i_{cp}	1	A
		$PW \leq 300\mu s, Duty$	
		$Cycle \geq 10\%$	
Collector Dissipation	P_C	25	W
Junction Temperature	T_J	150	$^\circ C$
Storage Temperature	T_{stg}	-55 to +150	$^\circ C$


Electrical Characteristics at $T_a=25^\circ C$

			min	typ	max	unit
Collector Cutoff Current	I_{CBO}	$V_{CB}=800V, I_E=0$			10	μA
Emitter Cutoff Current	I_{EBO}	$V_{EB}=5V, I_C=0$			10	μA
DC Current Gain	$h_{FE(1)}$	$V_{CE}=5V, I_C=20mA$	10*		40*	
	$h_{FE(2)}$	$V_{CE}=5V, I_C=100mA$	8			
C-E Saturation Voltage	$V_{CE(sat)}$	$I_C=100mA, I_B=20mA$			2.0	V
Gain-Bandwidth Product	f_T	$V_{CE}=10V, I_C=20mA$		15		MHz
Output Capacitance	c_{ob}	$V_{CB}=10V, f=1MHz$		10		pF
C-B Breakdown Voltage	$V_{(BR)CBO}$	$I_C=1mA, I_E=0$	900			V
C-E Breakdown Voltage	$V_{(BR)CEO}$	$I_C=1mA, R_{BE}=\infty$	800			V
E-B Breakdown Voltage	$V_{(BR)EBO}$	$I_E=1mA, I_C=0$	7			V
C-E Sustain Voltage	$V_{CEO(sus)}$	$I_C=0.2A, I_B=0.04A, L=10mH$	800			V
	$V_{CEX(sus)}$	$I_C=0.2A, I_{B1}=0.04A, I_{B2}=-0.04A, L=10mH, clamped$	900			V
Turn-on Time	t_{on}	$I_C=200mA, I_{B1}=40mA, I_{B2}=-80mA$			1.0	μs
Storage Time	t_{stg}	" "			3.0	μs
Fall Time	t_f	" "			1.0	μs

*: The $h_{FE(1)}$ of the 2SC3183 is classified as follows. When specifying the $h_{FE(1)}$ rank, specify two ranks or more in principle.


10	K	20	15	L	30	20	M	40
----	---	----	----	---	----	----	---	----









Switching Time Test Circuit





Unit (Resistance : Ω , Capacitance : F)

Package Dimensions 2010A (unit:mm)







- No products described or contained herein are intended for use in surgical implants, life-support systems, aerospace equipment, nuclear power control systems, vehicles, disaster/crime-prevention equipment and the like, the failure of which may directly or indirectly cause injury, death or property loss.
- Anyone purchasing any products described or contained herein for an above-mentioned use shall:
 - ① Accept full responsibility and indemnify and defend SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors and all their officers and employees, jointly and severally, against any and all claims and litigation and all damages, cost and expenses associated with such use;
 - ② Not impose any responsibility for any fault or negligence which may be cited in any such claim or litigation on SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors or any of their officers and employees jointly or severally.
- Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.