

DATA SHEET

NEC

NPN SILICON RF TRANSISTOR 2SC5509

NPN SILICON RF TRANSISTOR FOR MEDIUM OUTPUT POWER · LOW NOISE · HIGH-GAIN AMPLIFICATION FLAT-LEAD 4-PIN THIN-TYPE SUPER MINIMOLD

FEATURES

- Ideal for medium output power amplification
- $NF = 1.2 \text{ dB TYP.}$, $G_a = 12 \text{ dB TYP.}$ @ $V_{CE} = 2 \text{ V}$, $I_c = 10 \text{ mA}$, $f = 2 \text{ GHz}$
- Maximum available power gain: $MAG = 14 \text{ dB TYP.}$ @ $V_{CE} = 2 \text{ V}$, $I_c = 50 \text{ mA}$, $f = 2 \text{ GHz}$
- $f_T = 25 \text{ GHz}$ technology adopted
- Flat-lead 4-pin thin-type super minimold package

ORDERING INFORMATION

Part Number	Quantity	Supplying Form
2SC5509	50 pcs (Non reel)	<ul style="list-style-type: none"> • 8 mm wide embossed taping • Pin 1 (Emitter), Pin 2 (Collector) face the perforation side of the tape
2SC5509-T2	3 kpcs/reel	

Remark To order evaluation samples, contact your nearby sales office.
The unit sample quantity is 50 pcs.

ABSOLUTE MAXIMUM RATINGS ($T_A = +25^\circ\text{C}$)

Parameter	Symbol	Ratings	Unit
Collector to Base Voltage	V_{CBO}	15	V
Collector to Emitter Voltage	V_{CEO}	3.3	V
Emitter to Base Voltage	V_{EBO}	1.5	V
Collector Current	I_c	100	mA
Total Power Dissipation	P_{tot} <small>Note</small>	190	mW
Junction Temperature	T_j	150	$^\circ\text{C}$
Storage Temperature	T_{stg}	-65 to +150	$^\circ\text{C}$

Note Free Air

Because this product uses high-frequency technology, avoid excessive static electricity, etc.

The information in this document is subject to change without notice. Before using this document, please confirm that this is the latest version.
Not all devices/types available in every country. Please check with local NEC Compound Semiconductor Devices representative for availability and additional information.

THERMAL RESISTANCE

Parameter	Symbol	Ratings	Unit
Junction to Case Resistance	R _{th j-c}	95	°C/W
Junction to Ambient Resistance	R _{th j-a}	650	°C/W

ELECTRICAL CHARACTERISTICS (T_A = +25°C)

Parameter	Symbol	Test Conditions	MIN.	TYP.	MAX.	Unit
DC Characteristics						
Collector Cut-off Current	I _{CB0}	V _{CB} = 5 V, I _E = 0 mA	–	–	600	nA
Emitter Cut-off Current	I _{EB0}	V _{BE} = 1 V, I _C = 0 mA	–	–	600	nA
DC Current Gain	h _{FE} ^{Note 1}	V _{CE} = 2 V, I _C = 10 mA	50	70	100	–
RF Characteristics						
Gain Bandwidth Product	f _T	V _{CE} = 3 V, I _C = 90 mA, f = 2 GHz	13	15	–	GHz
Insertion Power Gain	S _{21e} ²	V _{CE} = 2 V, I _C = 50 mA, f = 2 GHz	8	11	–	dB
Noise Figure	NF	V _{CE} = 2 V, I _C = 10 mA, f = 2 Hz, Z _S = Z _{opt}	–	1.2	1.7	dB
Reverse Transfer Capacitance	C _{re} ^{Note 2}	V _{CB} = 2 V, I _E = 0 mA, f = 1 MHz	–	0.5	0.75	pF
Maximum Available Power Gain	MAG ^{Note 3}	V _{CE} = 2 V, I _C = 50 mA, f = 2 GHz	–	14	–	dB
Maximum Stable Power Gain	MSG ^{Note 4}	V _{CE} = 2 V, I _C = 50 mA, f = 2 GHz	–	15	–	dB
Gain 1 dB Compression Output Power	P _{O(1 dB)}	V _{CE} = 2 V, I _C = 70 mA ^{Note 5} , f = 2 GHz	–	17	–	dBm
3rd Order Intermodulation Distortion Output Intercept Point	OIP ₃	V _{CE} = 2 V, I _C = 70 mA ^{Note 5} , f = 2 GHz	–	27	–	dBm

- Notes**
1. Pulse measurement: PW ≤ 350 μs, Duty Cycle ≤ 2%
 2. Collector to base capacitance when the emitter grounded

$$3. \text{ MAG} = \left| \frac{S_{21}}{S_{12}} \right| (K - \sqrt{K^2 - 1})$$

$$4. \text{ MSG} = \left| \frac{S_{21}}{S_{12}} \right|$$

5. Collector current when P_{O(1 dB)} is output


h_{FE} CLASSIFICATION

Rank	FB
Marking	T80
h _{FE} Value	50 to 100


TYPICAL CHARACTERISTICS (Unless otherwise specified, $T_A = +25^\circ\text{C}$)

Thermal/DC Characteristics


TOTAL POWER DISSIPATION vs. AMBIENT TEMPERATURE, CASE TEMPERATURE




COLLECTOR CURRENT vs. BASE TO EMITTER VOLTAGE



COLLECTOR CURRENT vs. COLLECTOR TO EMITTER VOLTAGE




DC CURRENT GAIN vs. COLLECTOR CURRENT




Capacitance/ft Characteristics

REVERSE TRANSFER CAPACITANCE vs. COLLECTOR TO BASE VOLTAGE




GAIN BANDWIDTH PRODUCT vs. COLLECTOR CURRENT




Gain Characteristics


INSERTION POWER GAIN, MAG, MSG vs. FREQUENCY



INSERTION POWER GAIN, MAG, MSG vs. COLLECTOR CURRENT




INSERTION POWER GAIN, MAG, MSG vs. COLLECTOR CURRENT




Output Characteristics

OUTPUT POWER, COLLECTOR CURRENT vs. INPUT POWER




OUTPUT POWER, COLLECTOR CURRENT vs. INPUT POWER




Noise Characteristics


NOISE FIGURE, ASSOCIATED GAIN vs. COLLECTOR CURRENT




NOISE FIGURE, ASSOCIATED GAIN vs. COLLECTOR CURRENT



NOISE FIGURE, ASSOCIATED GAIN vs. COLLECTOR CURRENT



NOISE FIGURE, ASSOCIATED GAIN vs. COLLECTOR CURRENT



Remark The graphs indicate nominal characteristics.

S-PARAMETERS

V_{CE} = 2 V, I_C = 5 mA

Frequency (GHz)	S ₁₁		S ₂₁		S ₁₂		S ₂₂	
	MAG.	ANG. (deg.)	MAG.	ANG. (deg.)	MAG.	ANG. (deg.)	MAG.	ANG. (deg.)
0.1	0.79	-28.2	14.75	161.9	0.03	72.3	0.93	-19.5
0.2	0.75	-53.3	13.32	147.0	0.05	60.2	0.84	-35.9
0.3	0.73	-74.8	11.81	134.8	0.07	50.9	0.74	-49.6
0.4	0.71	-92.9	10.40	124.5	0.08	42.8	0.65	-61.4
0.5	0.69	-108.1	9.18	116.0	0.09	36.7	0.58	-71.5
0.6	0.68	-121.0	8.15	108.6	0.09	31.7	0.51	-80.4
0.7	0.67	-132.0	7.28	102.3	0.10	27.8	0.46	-88.6
0.8	0.67	-141.6	6.55	96.6	0.10	24.7	0.42	-96.2
0.9	0.67	-149.9	5.94	91.5	0.10	21.8	0.38	-103.3
1.0	0.67	-157.3	5.42	86.9	0.10	19.7	0.35	-110.1
1.1	0.67	-164.0	4.97	82.6	0.11	17.7	0.33	-116.6
1.2	0.67	-170.0	4.59	78.6	0.11	16.0	0.31	-123.0
1.3	0.67	-175.5	4.25	74.9	0.11	14.6	0.30	-129.1
1.4	0.67	179.5	3.96	71.3	0.11	13.4	0.29	-134.9
1.5	0.68	174.7	3.70	67.9	0.11	12.3	0.28	-140.6
1.6	0.68	170.4	3.47	64.6	0.11	11.3	0.27	-146.1
1.7	0.69	166.2	3.26	61.4	0.11	10.4	0.27	-151.4
1.8	0.69	162.4	3.07	58.4	0.11	9.6	0.27	-156.5
1.9	0.69	158.8	2.90	55.5	0.11	8.9	0.27	-161.2
2.0	0.70	155.2	2.74	52.6	0.11	8.4	0.27	-165.8
2.1	0.71	152.2	2.60	49.8	0.11	7.7	0.27	-170.2
2.2	0.71	148.9	2.47	47.1	0.11	7.0	0.27	-174.2
2.3	0.72	146.0	2.35	44.4	0.11	6.5	0.28	-178.1
2.4	0.72	143.3	2.24	41.8	0.11	6.0	0.28	178.2
2.5	0.72	140.4	2.14	39.2	0.11	5.5	0.29	174.6
2.6	0.73	137.9	2.03	36.7	0.11	4.8	0.29	170.4
2.7	0.72	135.3	1.93	34.4	0.11	4.9	0.30	165.9
2.8	0.73	133.7	1.84	33.0	0.11	7.1	0.29	162.7
2.9	0.73	132.1	1.79	31.3	0.11	8.4	0.28	162.4
3.0	0.74	130.0	1.73	29.1	0.11	8.0	0.29	161.5
4.0	0.80	121.2	1.27	16.5	0.12	9.0	0.38	149.8

V_{CE} = 2 V, I_c = 10 mA

Frequency (GHz)	S ₁₁		S ₂₁		S ₁₂		S ₂₂	
	MAG.	ANG. (deg.)	MAG.	ANG. (deg.)	MAG.	ANG. (deg.)	MAG.	ANG. (deg.)
0.1	0.65	-42.0	23.47	156.3	0.03	67.9	0.88	-29.3
0.2	0.63	-75.4	19.87	138.3	0.04	53.8	0.75	-52.4
0.3	0.63	-100.3	16.55	125.1	0.05	45.8	0.63	-70.5
0.4	0.62	-118.7	13.88	115.1	0.06	39.3	0.54	-85.4
0.5	0.62	-132.8	11.82	107.2	0.07	35.3	0.48	-97.8
0.6	0.63	-144.0	10.22	100.7	0.07	32.5	0.43	-108.7
0.7	0.63	-153.1	8.97	95.1	0.07	30.7	0.40	-118.3
0.8	0.63	-160.9	7.96	90.3	0.07	29.3	0.37	-127.1
0.9	0.64	-167.5	7.15	86.0	0.08	28.2	0.36	-135.0
1.0	0.64	-173.5	6.47	82.0	0.08	27.5	0.34	-142.2
1.1	0.65	-178.7	5.89	78.4	0.08	26.8	0.34	-148.8
1.2	0.65	176.5	5.41	75.0	0.08	26.5	0.33	-154.9
1.3	0.65	172.1	4.99	71.7	0.08	25.9	0.33	-160.6
1.4	0.66	168.0	4.63	68.6	0.09	25.6	0.33	-165.8
1.5	0.67	164.2	4.32	65.6	0.09	25.3	0.33	-170.6
1.6	0.67	160.7	4.04	62.8	0.09	24.8	0.33	-175.0
1.7	0.68	157.2	3.79	60.0	0.09	24.3	0.33	-179.2
1.8	0.68	154.0	3.56	57.3	0.09	23.9	0.34	176.9
1.9	0.69	151.0	3.36	54.7	0.10	23.4	0.34	173.3
2.0	0.69	148.0	3.17	52.1	0.10	23.1	0.35	169.8
2.1	0.70	145.4	3.01	49.7	0.10	22.7	0.35	166.7
2.2	0.70	142.6	2.86	47.3	0.10	21.9	0.36	163.7
2.3	0.71	140.1	2.71	44.9	0.10	21.4	0.37	160.8
2.4	0.71	137.7	2.58	42.5	0.10	20.9	0.37	158.0
2.5	0.72	135.1	2.46	40.2	0.11	20.2	0.38	155.2
2.6	0.72	132.9	2.34	37.9	0.11	19.6	0.39	152.2
2.7	0.72	130.5	2.22	35.8	0.11	19.7	0.39	148.9
2.8	0.72	129.0	2.11	34.6	0.11	21.2	0.39	145.9
2.9	0.73	127.8	2.05	33.1	0.11	21.6	0.38	145.0
3.0	0.74	126.0	1.99	31.1	0.12	20.6	0.39	144.3
4.0	0.80	118.7	1.45	19.9	0.13	17.6	0.47	136.2
5.0	0.83	107.5	1.09	5.8	0.14	13.1	0.53	125.3

$V_{CE} = 2\text{ V}$, $I_c = 20\text{ mA}$


Frequency (GHz)	S ₁₁		S ₂₁		S ₁₂		S ₂₂	
	MAG.	ANG. (deg.)	MAG.	ANG. (deg.)	MAG.	ANG. (deg.)	MAG.	ANG. (deg.)
0.1	0.50	-63.8	33.35	149.5	0.02	64.8	0.81	-41.4
0.2	0.54	-103.8	25.91	129.5	0.03	50.4	0.65	-71.4
0.3	0.57	-127.4	20.30	116.5	0.04	44.2	0.55	-93.1
0.4	0.59	-142.7	16.37	107.3	0.04	41.0	0.48	-109.7
0.5	0.60	-153.8	13.60	100.5	0.05	39.5	0.44	-122.8
0.6	0.61	-162.3	11.58	94.9	0.05	39.0	0.42	-133.6
0.7	0.61	-169.2	10.05	90.1	0.05	38.8	0.40	-142.6
0.8	0.62	-175.1	8.86	86.0	0.06	38.9	0.39	-150.4
0.9	0.63	179.8	7.91	82.2	0.06	38.8	0.39	-157.1
1.0	0.63	175.2	7.12	78.8	0.06	38.8	0.38	-163.0
1.1	0.64	171.1	6.47	75.6	0.07	38.7	0.38	-168.3
1.2	0.64	167.2	5.93	72.5	0.07	38.6	0.38	-173.1
1.3	0.65	163.7	5.46	69.6	0.07	38.3	0.39	-177.5
1.4	0.66	160.3	5.06	66.9	0.08	38.0	0.39	178.5
1.5	0.66	157.1	4.70	64.1	0.08	37.5	0.40	174.8
1.6	0.67	154.1	4.40	61.6	0.08	37.0	0.40	171.4
1.7	0.67	151.2	4.12	59.0	0.09	36.3	0.41	168.2
1.8	0.68	148.5	3.87	56.5	0.09	35.7	0.41	165.1
1.9	0.68	145.8	3.65	54.2	0.09	35.0	0.42	162.2
2.0	0.69	143.2	3.44	51.8	0.10	34.3	0.42	159.5
2.1	0.70	140.9	3.26	49.5	0.10	33.5	0.43	156.9
2.2	0.70	138.4	3.10	47.3	0.10	32.5	0.44	154.4
2.3	0.71	136.2	2.94	45.1	0.10	31.7	0.45	152.0
2.4	0.71	134.0	2.80	42.9	0.11	30.8	0.45	149.6
2.5	0.72	131.6	2.66	40.7	0.11	29.8	0.46	147.3
2.6	0.72	129.6	2.53	38.6	0.11	28.9	0.47	144.8
2.7	0.72	127.3	2.41	36.6	0.11	28.6	0.48	142.0
2.8	0.72	125.8	2.28	35.5	0.11	29.6	0.47	139.1
2.9	0.72	124.9	2.22	34.4	0.12	29.9	0.46	138.1
3.0	0.74	123.4	2.16	32.4	0.12	28.1	0.47	137.6
4.0	0.80	116.8	1.54	22.1	0.13	23.2	0.55	130.3
5.0	0.83	106.4	1.16	8.9	0.14	15.7	0.60	119.8

V_{CE} = 2 V, I_c = 50 mA


Frequency (GHz)	S ₁₁		S ₂₁		S ₁₂		S ₂₂	
	MAG.	ANG. (deg.)	MAG.	ANG. (deg.)	MAG.	ANG. (deg.)	MAG.	ANG. (deg.)
0.1	0.39	-99.2	41.74	143.0	0.02	59.2	0.71	-55.1
0.2	0.51	-133.4	29.88	122.2	0.03	50.6	0.57	-90.5
0.3	0.56	-150.6	22.35	110.1	0.03	48.2	0.50	-113.6
0.4	0.58	-161.3	17.59	102.0	0.03	47.8	0.46	-129.7
0.5	0.60	-169.1	14.41	96.0	0.04	48.3	0.44	-141.6
0.6	0.61	-175.2	12.16	91.0	0.04	48.7	0.43	-150.8
0.7	0.62	179.7	10.50	86.9	0.05	49.1	0.43	-158.3
0.8	0.62	175.2	9.22	83.2	0.05	49.6	0.43	-164.6
0.9	0.63	171.3	8.20	79.8	0.05	49.7	0.43	-169.9
1.0	0.64	167.6	7.38	76.7	0.06	49.5	0.43	-174.7
1.1	0.64	164.2	6.70	73.7	0.06	49.0	0.43	-178.9
1.2	0.65	161.0	6.12	70.9	0.07	48.7	0.44	177.3
1.3	0.65	158.0	5.63	68.2	0.07	48.0	0.44	173.8
1.4	0.66	155.2	5.21	65.6	0.07	47.2	0.45	170.5
1.5	0.67	152.4	4.84	63.1	0.08	46.5	0.45	167.4
1.6	0.67	149.8	4.52	60.7	0.08	45.5	0.46	164.5
1.7	0.68	147.1	4.23	58.3	0.09	44.4	0.46	161.8
1.8	0.68	144.8	3.98	55.9	0.09	43.5	0.47	159.1
1.9	0.69	142.4	3.75	53.7	0.09	42.3	0.48	156.7
2.0	0.70	140.0	3.54	51.5	0.10	41.3	0.48	154.2
2.1	0.70	137.9	3.35	49.3	0.10	40.1	0.49	152.0
2.2	0.71	135.6	3.18	47.2	0.10	38.9	0.50	149.8
2.3	0.71	133.5	3.02	45.1	0.11	37.8	0.51	147.6
2.4	0.72	131.5	2.87	43.0	0.11	36.6	0.51	145.5
2.5	0.72	129.3	2.73	40.9	0.11	35.4	0.52	143.4
2.6	0.73	127.4	2.60	38.9	0.11	34.4	0.53	141.1
2.7	0.73	125.1	2.47	36.9	0.11	33.6	0.53	138.6
2.8	0.72	123.4	2.33	35.8	0.11	34.3	0.53	135.7
2.9	0.72	122.9	2.26	35.1	0.12	34.4	0.52	134.7
3.0	0.74	121.6	2.21	33.2	0.13	32.2	0.53	134.4
4.0	0.81	115.4	1.52	23.2	0.14	25.7	0.62	126.9
5.0	0.84	105.2	1.14	10.8	0.15	17.6	0.66	126.5

EQUAL NF CIRCLE

$V_{CE} = 2\text{ V}$
 $I_c = 10\text{ mA}$
 $f = 1\text{ GHz}$



$V_{CE} = 2\text{ V}$
 $I_c = 10\text{ mA}$
 $f = 2\text{ GHz}$



NOISE PARAMETERS

$V_{CE} = 2\text{ V}$, $I_c = 5\text{ mA}$

f (GHz)	NF _{min} (dB)	G _a (dB)	Γ _{opt}		Rn/50
			MAG.	ANG.	
0.8	0.70	18.0	0.17	93.0	0.11
0.9	0.74	17.0	0.18	103.0	0.11
1.0	0.78	16.2	0.20	112.7	0.11
1.5	0.98	13.6	0.32	155.4	0.09
1.8	1.10	12.5	0.40	176.2	0.07
1.9	1.14	12.2	0.43	-177.8	0.06
2.0	1.18	11.8	0.46	-172.2	0.06
2.5	1.39	9.9	0.56	-151.8	0.08

$V_{CE} = 2\text{ V}$, $I_c = 20\text{ mA}$

f (GHz)	NF _{min} (dB)	G _a (dB)	Γ _{opt}		Rn/50
			MAG.	ANG.	
0.8	1.12	20.7	0.30	-164.8	0.08
0.9	1.15	19.7	0.31	-162.7	0.09
1.0	1.18	18.8	0.32	-160.7	0.09
1.5	1.31	15.7	0.39	-151.5	0.10
1.8	1.38	14.4	0.45	-146.3	0.10
1.9	1.41	14.0	0.47	-144.6	0.10
2.0	1.43	13.6	0.49	-142.9	0.11
2.5	1.56	11.5	0.56	-133.5	0.14

$V_{CE} = 2\text{ V}$, $I_c = 10\text{ mA}$



f (GHz)	NF _{min} (dB)	G _a (dB)	Γ _{opt}		Rn/50
			MAG.	ANG.	
0.8	0.87	19.6	0.13	170.3	0.09
0.9	0.90	18.6	0.15	171.5	0.09
1.0	0.93	17.8	0.17	173.0	0.09
1.5	1.07	14.8	0.30	-174.1	0.08
1.8	1.15	13.6	0.39	-164.1	0.07
1.9	1.18	13.2	0.41	-160.6	0.07
2.0	1.20	12.8	0.44	-157.2	0.07
2.5	1.35	10.9	0.53	-142.3	0.10

$V_{CE} = 2\text{ V}$, $I_c = 50\text{ mA}$

f (GHz)	NF _{min} (dB)	G _a (dB)	Γ _{opt}		Rn/50
			MAG.	ANG.	
0.8	1.75	21.3	0.49	-159.4	0.10
0.9	1.78	20.3	0.49	-157.2	0.10
1.0	1.80	19.4	0.50	-154.9	0.11
1.5	1.92	16.2	0.55	-144.7	0.14
1.8	2.00	14.8	0.59	-139.1	0.17
1.9	2.02	14.4	0.60	-137.3	0.19
2.0	2.04	13.9	0.61	-135.5	0.20
2.5	2.17	11.8	0.65	-126.4	0.28

PACKAGE DIMENSIONS

FLAT-LEAD 4-PIN THIN-TYPE SUPER MINIMOLD (UNIT: mm)



PIN CONNECTIONS

1. Emitter
2. Collector
3. Emitter
4. Base

RECOMMENDED SOLDERING CONDITIONS

This product should be soldered and mounted under the following recommended conditions. For soldering methods and conditions other than those recommended below, contact your nearby sales office.

Soldering Method	Soldering Conditions	Recommended Condition Symbol
Infrared Reflow	Package peak temperature: 235°C or below, Time: 30 seconds or less (at 210°C or higher), Count: 2 times or less, Exposure limit: None ^{Note}	IR30-00-2
VPS	Package peak temperature: 215°C or below, Time: 40 seconds or less (at 200°C or higher), Count: 2 times or less, Exposure limit: None ^{Note}	VP15-00-2
Wave Soldering	Soldering bath temperature: 260°C or below, Time: 10 seconds or less, Count: 1 time, Exposure limit: None ^{Note}	WS60-00-1

Note After opening the dry pack, store it at 25°C or less and 65% RH or less for the allowable storage period.

Caution Do not use different soldering methods together (except for partial heating).

For the details the recommended soldering conditions, refer to the document **SEMICONDUCTOR DEVICE MOUNTING TECHNOLOGY MANUAL (C10535E: published by NEC Corporation)**.

- **The information in this document is current as of October, 2001. The information is subject to change without notice. For actual design-in, refer to the latest publications of NEC's data sheets or data books, etc., for the most up-to-date specifications of NEC semiconductor products. Not all products and/or types are available in every country. Please check with an NEC sales representative for availability and additional information.**
 - No part of this document may be copied or reproduced in any form or by any means without prior written consent of NEC. NEC assumes no responsibility for any errors that may appear in this document.
 - NEC does not assume any liability for infringement of patents, copyrights or other intellectual property rights of third parties by or arising from the use of NEC semiconductor products listed in this document or any other liability arising from the use of such products. No license, express, implied or otherwise, is granted under any patents, copyrights or other intellectual property rights of NEC or others.
 - Descriptions of circuits, software and other related information in this document are provided for illustrative purposes in semiconductor product operation and application examples. The incorporation of these circuits, software and information in the design of customer's equipment shall be done under the full responsibility of customer. NEC assumes no responsibility for any losses incurred by customers or third parties arising from the use of these circuits, software and information.
 - While NEC endeavours to enhance the quality, reliability and safety of NEC semiconductor products, customers agree and acknowledge that the possibility of defects thereof cannot be eliminated entirely. To minimize risks of damage to property or injury (including death) to persons arising from defects in NEC semiconductor products, customers must incorporate sufficient safety measures in their design, such as redundancy, fire-containment, and anti-failure features.
 - NEC semiconductor products are classified into the following three quality grades:
 "Standard", "Special" and "Specific". The "Specific" quality grade applies only to semiconductor products developed based on a customer-designated "quality assurance program" for a specific application. The recommended applications of a semiconductor product depend on its quality grade, as indicated below. Customers must check the quality grade of each semiconductor product before using it in a particular application.
 "Standard": Computers, office equipment, communications equipment, test and measurement equipment, audio and visual equipment, home electronic appliances, machine tools, personal electronic equipment and industrial robots
 "Special": Transportation equipment (automobiles, trains, ships, etc.), traffic control systems, anti-disaster systems, anti-crime systems, safety equipment and medical equipment (not specifically designed for life support)
 "Specific": Aircraft, aerospace equipment, submersible repeaters, nuclear reactor control systems, life support systems and medical equipment for life support, etc.
- The quality grade of NEC semiconductor products is "Standard" unless otherwise expressly specified in NEC's data sheets or data books, etc. If customers wish to use NEC semiconductor products in applications not intended by NEC, they must contact an NEC sales representative in advance to determine NEC's willingness to support a given application.
- (Note)
- (1) "NEC" as used in this statement means NEC Corporation, NEC Compound Semiconductor Devices, Ltd. and also includes its majority-owned subsidiaries.
 - (2) "NEC semiconductor products" means any semiconductor product developed or manufactured by or for NEC (as defined above).

M8E 00.4-0110

► **Business issue**

NEC Compound Semiconductor Devices, Ltd.

5th Sales Group, Sales Division TEL: +81-3-3798-6372 FAX: +81-3-3798-6783 E-mail: salesinfo@csd-nec.com

NEC Compound Semiconductor Devices Hong Kong Limited

Hong Kong Head Office TEL: +852-3107-7303 FAX: +852-3107-7309

Taipei Branch Office TEL: +886-2-8712-0478 FAX: +886-2-2545-3859

Korea Branch Office TEL: +82-2-528-0301 FAX: +82-2-528-0302

NEC Electron Devices European Operations <http://www.nec.de/>

TEL: +49-211-6503-101 FAX: +49-211-6503-487

California Eastern Laboratories, Inc. <http://www.cel.com/>

TEL: +1-408-988-3500 FAX: +1-408-988-0279

► **Technical issue**

NEC Compound Semiconductor Devices, Ltd. <http://www.csd-nec.com/>

Sales Engineering Group, Sales Division

E-mail: techinfo@csd-nec.com FAX: +81-44-435-1918