

SANYO	No.2115B	2SD1805
	NPN Epitaxial Planar Silicon Transistor High-Current Switching Applications	

Applications

- Strobes, voltage regulators, relay drivers, lamp drivers

Features

- Low saturation voltage
- Fast switching time
- Large current capacity
- Small and slim package making it easy to make 2SD1805-applied sets smaller

Absolute Maximum Ratings at Ta = 25°C

			unit
Collector to Base Voltage	V _{CB0}	60	V
Collector to Emitter Voltage	V _{CEO}	20	V
Emitter to Base Voltage	V _{EBO}	6	V
Collector Current	I _C	5	A
Collector Current(Pulse)	I _{CP}	8	A
Collector Dissipation	P _C	1	W
		15	W
Junction Temperature	T _j	150	°C
Storage Temperature	T _{stg}	-55 to +150	°C

T_c = 25°C

Electrical Characteristics at Ta = 25°C

			min	typ	max	unit
Collector Cutoff Current	I _{CBO}	V _{CB} = 50V, I _E = 0			100	nA
Emitter Cutoff Current	I _{EBO}	V _{EB} = 5V, I _C = 0			100	nA
DC Current Gain	h _{FE} (1)	V _{CE} = 2V, I _C = 500mA	120*		560*	
	h _{FE} (2)	V _{CE} = 2V, I _C = 3A	95			
Gain-Bandwidth Product	f _T	V _{CE} = 10V, I _C = 50mA		120		MHz
Output Capacitance	c _{ob}	V _{CB} = 10V, f = 1MHz		45		pF
C-E Saturation Voltage	V _{CE(sat)}	I _C = 3A, I _B = 60mA	220	500		mV
B-E Saturation Voltage	V _{BE(sat)}	I _C = 3A, I _B = 60mA		1.5		V
C-B Breakdown Voltage	V _{(BR)CBO}	I _C = 10μA, I _E = 0	60			V
C-E Breakdown Voltage	V _{(BR)CEO}	I _C = 1mA, R _{BE} = ∞	20			V
E-B Breakdown Voltage	V _{(BR)EBO}	I _E = 10μA, I _C = 0	6			V


Continued on next page.

*: The 2SD1805 is classified by 500mA h_{FE} as follows:

120 E 200	160 F 320	280 G 560
-----------	-----------	-----------


Package Dimensions 2045B

(unit: mm)



Package Dimensions 2044B


(unit: mm)









Continued from preceding page.





			min	typ	max	unit
Turn-on Time	t_{on}	See specified Test Circuit.		30		ns
Storage Time	t_{stg}	"		300		ns
Fall Time	t_f	"		40		ns

Switching Time Test Circuit



Unit (Capacitance : F)
 $I_C = 10 I_{B1} = -10 I_{B2} = 2A, V_{CC} = 10V$





- No products described or contained herein are intended for use in surgical implants, life-support systems, aerospace equipment, nuclear power control systems, vehicles, disaster/crime-prevention equipment and the like, the failure of which may directly or indirectly cause injury, death or property loss.
- Anyone purchasing any products described or contained herein for an above-mentioned use shall:
 - ① Accept full responsibility and indemnify and defend SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors and all their officers and employees, jointly and severally, against any and all claims and litigation and all damages, cost and expenses associated with such use:
 - ② Not impose any responsibility for any fault or negligence which may be cited in any such claim or litigation on SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors or any of their officers and employees jointly or severally.
- Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.