

<b>SANYO</b>	No.2533	2SD1940
	NPN Epitaxial Planar Type Silicon Transistor	
HIGH-VOLTAGE SWITCHING, AF25 TO 30W OUTPUT APPLICATIONS		

**Features**

- . Micaless package facilitating mounting
- . Wide ASO

**Absolute Maximum Ratings at Ta=25°C**

Collector-to-Base Voltage	V <sub>CB0</sub>	100	V	unit
Collector-to-Emitter Voltage	V <sub>CE0</sub>	85	V	
Emitter-to-Base Voltage	V <sub>EB0</sub>	6	V	
Collector Current	I <sub>C</sub>	6	A	
Peak Collector Current	i <sub>cp</sub>	10	A	
Collector Dissipation	P <sub>C</sub>	25	W	Tc=25°C
Junction Temperature	T <sub>J</sub>	150	°C	
Storage Temperature	T <sub>stg</sub>	-55 to +150	°C	


**Electrical Characteristics at Ta=25°C**

		min	typ	max	unit
Collector Cutoff Current	I <sub>CB0</sub> V <sub>CB</sub> =40V, I <sub>E</sub> =0			0.1	mA
Emitter Cutoff Current	I <sub>EB0</sub> V <sub>EB</sub> =4V, I <sub>C</sub> =0			0.1	mA
DC Current Gain	h <sub>FE</sub> (1) V <sub>CE</sub> =5V, I <sub>C</sub> =1A	60*		320*	
	h <sub>FE</sub> (2) V <sub>CE</sub> =5V, I <sub>C</sub> =3A	20			
Gain-Bandwidth Product	f <sub>T</sub> V <sub>CE</sub> =5V, I <sub>C</sub> =1A		15		MHz
C-E Saturation Voltage	V <sub>CE(sat)</sub> I <sub>C</sub> =4A, I <sub>B</sub> =0.4A			2.0	V
Base to Emitter Voltage	V <sub>BE</sub> V <sub>CE</sub> =5V, I <sub>C</sub> =1A			1.5	V
Output Capacitance	c <sub>ob</sub> V <sub>CB</sub> =10V, f=1MHz		110		pF
C-B Breakdown Voltage	V(BR)CBO I <sub>C</sub> =5mA, I <sub>E</sub> =0	100			V
C-E Breakdown Voltage	V(BR)CEO I <sub>C</sub> =5mA, R <sub>BE</sub> =∞	85			V
E-B Breakdown Voltage	V(BR)EBO I <sub>E</sub> =5mA, I <sub>C</sub> =0	6			V
Turn-on Time	t <sub>on</sub> See specified Test Circuit.		0.28		μs
Fall Time	t <sub>f</sub> "		0.50		μs
Storage Time	t <sub>stg</sub> "		3.60		μs

\*: The 2SD1940 is classified by 1A h<sub>FE</sub> as follows:


60 D 120	100 E 200	160 F 320
----------	-----------	-----------









**Switching Time Test Circuit**




**Package Dimensions 2041**

(unit:mm)







- No products described or contained herein are intended for use in surgical implants, life-support systems, aerospace equipment, nuclear power control systems, vehicles, disaster/crime-prevention equipment and the like, the failure of which may directly or indirectly cause injury, death or property loss.
- Anyone purchasing any products described or contained herein for an above-mentioned use shall:
  - ① Accept full responsibility and indemnify and defend SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors and all their officers and employees, jointly and severally, against any and all claims and litigation and all damages, cost and expenses associated with such use:
  - ② Not impose any responsibility for any fault or negligence which may be cited in any such claim or litigation on SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors or any of their officers and employees jointly or severally.
- Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.