



**12C8**

**12C8  
TO  
12J5-GT**

**TWIN DIODE—REMOTE-CUTOFF PENTODE**

Heater, for Unipotential Cathode:		
Voltage . . . . .	12.6 . . . . .	ac or dc volts
Current . . . . .	0.15 . . . . .	amp

*The 12C8 is the same as the 6B8 except for heater rating.*

**12F5-GT  
HIGH-MU TRIODE**

Heater, for Unipotential Cathode:		
Voltage . . . . .	12.6 . . . . .	ac or dc volts
Current . . . . .	0.15 . . . . .	amp

*The 12F5-GT is the same as the 6F5-GT except for heater rating.*

**12H6  
TWIN DIODE**

Heater, for Unipotential Cathodes:		
Voltage . . . . .	12.6 . . . . .	ac or dc volts
Current . . . . .	0.15 . . . . .	amp

*The 12H6 is the same as the 6H6 except for heater rating.*

**12J5-GT  
MEDIUM-MU TRIODE**

Heater, for Unipotential Cathode:		
Voltage . . . . .	12.6 . . . . .	ac or dc volts
Current . . . . .	0.15 . . . . .	amp

*The 12J5-GT is the same as the 6J5-GT except for heater rating and base. Base and connections for the 12J5-GT are the same as for the 6P5-GT.*