

# 6FM7

## Dual Triode With High-Mu Unit and Low-Mu Unit

### Electrical:

#### DUODECAR TYPE


Heater Characteristics and Ratings:  
 Voltage (AC or DC) . . . . . 6.3 ± 0.6 volts  
 Current at 6.3 volts . . . . . 1.050 amp  
 Maximum heater-cathode voltage (Each unit):  
 Heater negative with respect to cathode:  
 Peak . . . . . 200 volts  
 Heater positive with respect to cathode:  
 Peak . . . . . 200 volts  
 DC component . . . . . 100 volts  
 Direct Interelectrode Capacitances (Approx.):<sup>a</sup>

	Unit No. 1	Unit No. 2
Grid to plate . . . . .	4.0	7.0 pf
Input: G to (K, H) . . . . .	2.4	7.0 pf
Output: P to (K, H) . . . . .	0.4	1.1 pf

### Mechanical:

Operating Position . . . . . Any  
 Type of Cathodes . . . . . Coated Unipotential  
 Maximum Overall Length . . . . . 2.375"  
 Seated Length . . . . . 1.750" to 2.000"  
 Diameter . . . . . 1.062" to 1.188"  
 Dimensional Outline (JEDEC 9-58) . . . . . See General Section  
 Bulb . . . . . T9  
 Base . . . . . Small-Button Duodecar 12-Pin (JEDEC No. E12-70)  
 Basing Designation for BOTTOM VIEW . . . . . 12EJ

- Pin 1 - Heater
- Pin 2 - No Internal Connection
- Pin 3 - Grid of Unit No. 2
- Pin 4 - No Internal Connection
- Pin 5 - Plate of Unit No. 2
- Pin 6 - Do Not Use
- Pin 7 - Cathode of Unit No. 2
- Pin 8 - Grid of Unit No. 2
- Pin 9 - Cathode of Unit No. 1
- Pin 10 - Grid of Unit No. 1
- Pin 11 - Plate of Unit No. 1
- Pin 12 - Heater



### Characteristics, Class A<sub>1</sub> Amplifier:

	Unit No. 1	Unit No. 2
Plate Voltage . . . . .	250	60 175 volts
Grid Voltage . . . . .	-3	0 <sup>b</sup> -25 volts
Amplification Factor . . . . .	66	- 5.5
Plate Resistance (Approx.) . . . . .	30000	- 920 ohms
Transconductance . . . . .	2200	- 6000 $\mu$ hos
Plate Current . . . . .	2	95 40 ma
Grid-Voltage (Approx.) for plate:		
$\mu$ A = 20 . . . . .	-5.3	- - volts
$\mu$ A = 200 . . . . .	- -	-45 volts



RADIO CORPORATION OF AMERICA  
 Electronic Components and Devices

Harrison, N. J.

DATA  
 5-65

# 6FM7

---

## VERTICAL DEFLECTION OSCILLATOR AND AMPLIFIER

### Maximum Ratings, Design-Maximum Values:

For operation in a 525-line, 30-frame system

	Unit No. 1 (Oscillator)	Unit No. 2 (Amplifier)	
DC Plate Voltage . . . . .	350	550	volts
Peak Positive-Pulse Plate Voltage. . . . .	-	1500 <sup>c</sup>	volts
Peak Negative Pulse-Grid Voltage. . . . .	400	250	volts
Cathode Current:			
Peak . . . . .	-	175	ma
Average. . . . .	-	50	ma
Plate Dissipation. . . . .	1	10 <sup>d</sup>	watts

### Maximum Circuit Values:

#### Grid-Circuit Resistance:

For fixed-bias operation .	1	1	megohm
For cathode-bias operation	2.2	2.2	megohms

<sup>a</sup> Without external shield.

<sup>b</sup> Applied for short interval (2 seconds maximum) so as not to damage tube.

<sup>c</sup> This rating is applicable where the duration of the voltage pulse does not exceed 15 per cent of one vertical scanning cycle. In a 525-line, 30-frame system, 15 per cent of one vertical scanning cycle is 2.5 milliseconds.

<sup>d</sup> An adequate bias resistor or other means is required to protect the tube in the absence of excitation.

---

DATA

RADIO CORPORATION OF AMERICA  
Electronic Components and Devices

Harrison, N. J.

